

## Filter-Table

- » Work bench with filter unit
- » Large working area



### Applications

- » Low to medium levels of smoke and dust
- » Occasional to frequent use
- » Welding and grinding

### Benefits

- » Maintenance door allows easy filter change
- » Minimized fire risk due to effective spark trap
- » Downdraft extraction throughout the whole working area
- » Wide range of applications due to large working area of 1200 x 800 mm

### Properties

- » Spark separator
- » Large, robust material support
- » Activated charcoal filter (optional)

### Order Data

Art. No.	Description
950 400 001	Filter-Table
109 0345	Activated charcoal filter (optional)
109 0013	Aluminum pre-filter
109 0010	Main filter

### Technical Data

Filter	
Filter stages	2
Filter method	Disposable filter
Filter surface	ca. 15.8 m <sup>2</sup>
Type of filter	Filter cassette
Filter material	Non-woven fibre
Filterclass	F9
Additional filters	Pre-filter (aluminum)
Basic data	
Extraction capacity	1.400 m <sup>3</sup> /h
Dimensions (w x d x h)	1,200 x 800 x 1,340 mm
Weight	155 kg
Motor power	1,5 kW
Power supply	3 x 400 V / 50 Hz
Rated current	3.2 A
Noise level	71 dB(A)
Additional information	
Fan type	Radial fan