

# MABasic 400

The high-speed machine - also suited for twist drills.














## The advantages of the MABasic 400


- > 1050 Watt motor
- > 2-stage gear unit with high rotation speed, ideal for working with twist drills
- > Core drilling from 12 mm to 35 mm – cutting depth 30 mm and 55 mm



### SPECIFICATION

	Motor output:	1050 Watt
	Voltage:	230 V AC, 50-60 Hz
	Stroke:	160 mm
	Swivel Base, adjustment feature:	–
	Magnet size:	84 x 168 x 41.5 mm
	Weight:	12 kg
	Direct arbor:	19 mm Weldon $\frac{3}{4}$ "
	Industrial arbor:	–
	Quick change drill chuck system:	–
	Morse taper:	–
	Speed range 1:	430 min <sup>-1</sup>
	Speed range 2:	760 min <sup>-1</sup>
	Speed range 3:	–
	Speed range 4:	–
	Permanent internal lubrication:	✓

	Friction clutch:	–
	Torque control:	–
	Full wave control electronics:	–
	Magnet indicator:	–
	Overheating protection:	–
	CW/CCW rotation:	–
	Core drill short 30 mm:	12 – 35 mm
	Core drill long 55 mm:	12 – 35 mm
	Core drill extra-long 110 mm:	–
	Twist drilling:	≤ ø 16 mm
	Reaming:	–
	Countersinking:	–
	Thread cutting:	–



Core drills ø 12 – 35 mm



Twist drills up to ø 16 mm



The practical carry case

### ORDER NO.

MABasic 400 / 230 Volt  
MABasic 400 / 110 Volt

### SCOPE OF DELIVERY

1 Magnetic core drilling machine	1 Hexagon Offset screwdriver SW 4
1 Ejector pin ZAK 075	1 Operating manual
1 Cutting oil pump bottle ZKP 100	
1 Plastic carry case	
1 Safety lashing strap	

Technical drawing: Page 42-43