



# TruTool TKF 700

Technical data

**TruTool TKF 700 30°  
bevel angle****TruTool TKF 700  
37.5° bevel angle****TruTool TKF 700 45°  
bevel angle****MAXIMUM CHAMFER LENGTHS**MAX. CHAMFER LENGTH, STEEL  
400 N/MM<sup>2</sup>

7 mm

7 mm

7 mm

MAX. CHAMFER LENGTH, STEEL  
600 N/MM<sup>2</sup>

5.7 mm

5.7 mm

5.7 mm

MAX. CHAMFER LENGTH, STEEL  
800 N/MM<sup>2</sup>

4 mm

4 mm

4 mm

**RADII**

SMALLEST RADIUS

40 mm

40 mm

40 mm

**GENERAL**

WORKING SPEED

1.5 m/min

1.5 m/min

1.5 m/min

STROKE RATE WITH NOMINAL  
LOAD

720 RPM

720 RPM

720 RPM

NOMINAL POWER CONSUMPTION

1400 W

1400 W

1400 W

SHEET THICKNESS

1 mm - 20 mm

1 mm - 20 mm

1 mm - 20 mm

**WEIGHT**

WEIGHT WITHOUT CABLE

5.4 kg

5.4 kg

5.4 kg

---

Subject to changes. The information in our offer and our order confirmation is definitive.