

YOUR PARTNER WORLDWIDE




TDF Series

PORTABLE FLANGE TURNING MACHINE WITH EXTERNAL CLAMPING



Numerous machining options




QUALITY, RELIABILITY AND INNOVATIVE TECHNOLOGY

Due to the constantly rising pressure on the costs of industrial maintenance, the demands made on the machines and tools required also increase.

The particular low profile and low weight of the portable TDF series turning machines create new possibilities for flange machining on site.

EFCO TDF machines are particularly suitable for:

- Machining of flanges of all types
- Valve housings
- Bottles
- Heat exchangers
- Fittings in shipbuilding
- Columns in refineries and the chemical industry
- Smooth and helically fluted flange sealing faces
- Internal cones and bores (special facing head)




TDF-2 with compressed air drive



TDF-2 with electric drive

Three different setup types:



Basic mounting on the flange bore

TDF machines can be mounted directly on the flange.

The machines can be aligned precisely with regard to the face to be machined using the integral adjustment system.

Chain clamping

If there is no flange, for example on Brettschneider closures, the chain tensioning system is the ideal solution.

The four clamping points required for mounting are provided by this system.

Mounting on tensioning blocks

Tensioning blocks are another universally adjustable clamping device for flanges with clearance holes. They form part of the scope of supply for many models of the TDF range.

Machine descriptions

	TDF-05	TDF-1	TDF-2	TDF-3
Face turning ranges	0-250 mm (0-9.8“)	0-500 mm (0-19.7“)	300-1200 mm (11.8“-47.2“)	700-2200 mm (27.5“-86.6“)

The low weight and low profile make mounting easier as this is normally handled by only one person. The machines are particularly suitable for the on-site repair of sealing faces of flanges in pipelines. The simply designed clamping and adjustment system permits mounting of the machines extremely quickly precisely centred and level to the flange.

Both machines are fitted with a facing head. It has 2 automatic feeds (0.1 mm (0.004”)/rotation for finishing and 1 mm (0.04”)/rotation for turning of spiral grooves or a surface roughness Rz 160 The cutting tool feed is 20 mm (0.8”) (50 mm (2”) for the TDF-3).

Indexable inserts with appropriate inserts are part of the standard equipment.

As an option, both machines can be fitted with an angled facing head.

The facing slide of this head can be continuously adjusted from 0° (facing) to 120°.

The stroke is 60 mm (2.36”).

This means that bores, too, can be machined at the 90° setting.



TDF-1



TDF-05-A

	TDF-05A	TDF-1A	TDF-2A
Face turning ranges	0-250 mm (0-9.8“)	0-400 mm (0-15.7“)	300-800 mm (11.8“-31.5“)

These machine types have an additional manual axial feed of 30 mm (1.2”). Despite this additional function, the machine height is only 310 mm (12.2”) (380 mm (15”) for the TDF-2A).

These models, too, can be mounted and operated by only one person without effort.

Due to the additional axial feed, the TDF-A machines are particularly suitable for cutting sealing grooves of all types.

Whilst the cutting tool feed on TDF machines can be operated only with the machine stationary, the axial feed which is arranged centrally to the machine, can also be moved with the cutting steel rotating.

The 2-feed facing head (0.1 mm (0.004”)/rotation and 1 mm (0.04”)/rotation) used on TDF machines is also used here.

As an option, the machines can be fitted with the angled facing head.



Angled facing head

All machines are low-maintenance and have lifetime lubrication.

Specifications - all dimensions in mm / inch

Type	TDF-05	TDF-05A	TDF-1	TDF-1A	TDF-2	TDF-2A	TDF-3
Machining dia.	0-250 0-9.8"	0-250 0-9.8"	0-500 0-19.7"	0-400 0-15.7"	300-1200 11.8"-47.2"	300-800 11.8"-31.5"	700-2200 27.5"-86.6"
Mounting dia.	250-400 9.8"-16"	250-400 9.8"-16"	260-600 10.2"-23.6"	260-600 10.2"-23.6"	480-1380 18.9"-54.3"	480-1380 18.9"-54.3"	750-2400 29.5"-94.5"
Machine height	230 9.1"	310 12.2"	230 9.1"	310 12.2"	300 11.8"	380 15"	450 17.7"
Radial stroke	80 3.15"	80 3.15"	80 3.15"	80 3.15"	100 3.9"	100 3.9"	150 5.9"
Radial feed, Fine (automatic)	0.1 0.004"	0.1 0.004"	0.1 0.004"	0.1 0.004"	0.1 0.004"	0.1 0.004"	0.1 0.004"
Radial feed, Coarse (automatic)	1 0.04"	1 0.04"	1 0.04"	1 0.04"	1 0.04"	1 0.04"	1 0.04"
Axial stroke (manual)	-	30 1.2"	-	30 1.2"	-	30 1.2"	-
Cutting tool feed	20 0.8"	-	20 0.8"	-	20 0.8"	-	50 2"
Axial stroke with angled head (optional)	60 2.36"	60 2.36"	60 2.36"	60 2.36"	80 3.15"	80 3.15"	80 3.15"
Shipping weight (kg)	48	61	54	67	270	300	485

All machines can be supplied with an electric as well as a compressed air drive.

Extensive accessories

All tools required for mounting are part of the scope of supply of the TDF machines. In addition, all TDF machines are equipped with a range of cutting tools.



Subject to technical change.

EFCO Maschinenbau GmbH – Valve repair and testing equipment

Otto-Brenner-Straße 5 – 7 • D - 52353 Düren • Phone: +49-(0)2421-989-0 • Fax: +49-(0)2421-86260

info@efco-dueren.de • sales@efco-dueren.de • www.efco-dueren.com

Agencies in many countries

12/2008 - 03